


コラムBCR295



寸法 (mm)		単位質量	断面積	断面2次モーメント	断面係数	断面2次半径	塑性断面係数
A×B	t	kg/m	cm ²	cm ⁴	cm ³	cm	Z _{px} =Z _{py} cm ³
200×200	6.0	35.6	45.32	2,800	280	7.86	327
	8.0	46.5	59.24	3,570	357	7.76	421
	9.0	51.8	65.98	3,920	392	7.71	465
	12.0	67.0	85.30	4,860	486	7.55	588
250×250	6.0	45.0	57.32	5,620	450	9.90	521
	9.0	65.9	83.98	7,980	639	9.75	750
	12.0	85.8	109.3	10,100	805	9.59	959
	16.0	111	141.0	12,400	992	9.38	1,210
300×300	6.0	54.4	69.32	9,890	660	11.9	760
	9.0	80.1	102.0	14,200	946	11.8	1,100
	12.0	105	133.3	18,100	1,200	11.6	1,420
	16.0	136	173.0	22,600	1,510	11.4	1,810
	19.0	158	201.2	25,500	1,700	11.3	2,070
350×350	9.0	94.2	120.0	23,000	1,310	13.8	1,520
	12.0	123	157.3	29,400	1,680	13.7	1,970
	16.0	161	205.0	37,200	2,130	13.5	2,530
	19.0	188	239.2	42,400	2,420	13.3	2,910
	22.0	214	272.0	47,100	2,690	13.2	3,270
400×400	9.0	108	138.0	34,800	1,740	15.9	2,010
	12.0	142	181.3	44,800	2,240	15.7	2,610
	16.0	186	237.0	57,100	2,850	15.5	3,370
	19.0	218	277.2	65,400	3,270	15.4	3,900
	22.0	248	316.0	73,000	3,650	15.2	4,390
450×450	12.0	161	205.3	64,800	2,880	17.8	3,340
	16.0	211	269.0	82,900	3,690	17.6	4,330
	19.0	247	315.2	95,500	4,240	17.4	5,020
	22.0	283	360.0	107,000	4,760	17.2	5,680
500×500	12.0	180	229.3	90,000	3,600	19.8	4,160
	16.0	236	301.0	116,000	4,630	19.6	5,410
	19.0	277	353.2	134,000	5,340	19.4	6,290
	22.0	317	404.0	150,000	6,010	19.3	7,130
550×550	16.0	261	333.0	156,000	5,670	21.6	6,610
	19.0	307	391.2	181,000	6,570	21.5	7,700
	22.0	352	448.0	204,000	7,420	21.3	8,750

各種ウラアテ在庫しております。