

# ガス管 配管用炭素鋼鋼管 SGP JIS G3452 (1988)

JIS呼称 記号A	インチ名 記号B	外径 mm	厚さ mm	質量	1本当り
				kg/m	kg/5.5m
6A□	1/8B	10.5□	2.0□	0.419□	2.30□
8A□	1/4B	13.8□	2.3□	0.652□	3.59□
10A□	3/8B	17.3□	2.3□	0.851□	4.68□
15A□	1/2B	21.7□	2.8□	1.31□	7.20□
20A□	3/4B	27.2□	2.8□	1.68□	9.24□
25A□	1B	34.0□	3.2□	2.43□	13.4□
32A□	1 1/4B	42.7□	3.5□	3.38□	18.6□
40A□	1 1/2B	48.6□	3.5□	3.89□	21.4□
50A□	2B	60.5□	3.8□	5.31□	29.2□
65A□	2 1/2B	76.3□	4.2□	7.47□	41.1□
80A□	3B	89.1□	4.2□	8.79□	48.3□
90A□	3 1/2B	101.6□	4.2□	10.1□	55.6□
100A□	4B	114.3□	4.5□	12.2□	67.1□
125A□	5B	139.8□	4.5□	15.0□	82.5□
150A□	6B	165.2□	5.0□	19.8□	109□
175A□	7B	190.7□	5.3□	24.2□	133□
200A□	8B	216.3□	5.8□	30.1□	166□
225A□	9B	241.8□	6.2□	36.0□	198□
250A□	10B	267.4□	6.6□	42.4□	233□
300A□	12B	318.5□	6.9□	53.0□	292□
350A□	14B	355.6□	7.9□	67.7□	372□
400A□	16B	406.4□	7.9□	77.6□	427□
450A□	18B	457.2□	7.9□	87.5□	481□
500A	20B	508.0	7.9	97.4	536

切断・開先加工も承ります。