


C形鋼

一般構造用軽量形鋼 JIS G3350(1987)

記号 SSC400



サイズ mm	厚さ mm	質量 kg/m		断面積 cm ²	重心位置 cm		断面2次 モーメント cm ⁴		断面2次半径 cm		断面係数 cm ³	
		黒かわ	メッキ		Cx	Cy	Ix	Iy	ix	iy	Zx	Zy
60×30×10	1.6	1.63	1.65	2.072	0	1.06	11.6	2.56	2.37	1.11	3.88	1.32
	2.3	2.25	2.27	2.872	0	1.06	15.6	3.32	2.33	1.07	5.20	1.71
75×45×15	1.6	2.32	2.35	2.950	0	1.72	27.1	8.71	3.03	1.72	7.24	3.13
	2.3	3.25	3.28	4.137	0	1.72	37.1	11.8	3.00	1.69	9.90	4.24
100×50×20	1.6	2.88	2.92	3.672	0	1.87	58.4	14.0	3.99	1.95	11.7	4.47
	2.3	4.06	4.10	5.172	0	1.86	80.7	19.0	3.95	1.92	16.1	6.07
	3.2	5.50	5.54	7.007	0	1.85	107	23.5	3.90	1.87	21.3	7.81
120×60×20	2.3	4.78		6.092	0	2.13	140	31.3	4.79	2.27	23.3	8.10
	3.2	6.51		8.287	0	2.12	186	40.9	4.74	2.22	31.0	10.5
125×50×20	2.3	4.51		5.747	0	1.69	137	20.6	4.88	1.89	21.9	6.22
	3.2	6.13	6.17	7.807	0	1.68	181	26.6	4.82	1.85	29.0	8.02
150×50×20	2.3	4.96		6.322	0	1.55	210	21.9	5.77	1.86	28.0	6.33
	3.2	6.76	6.81	8.607	0	1.54	280	28.3	5.71	1.81	37.4	8.19
150×65×20	3.2	7.51		9.567	0	2.11	332	53.8	5.89	2.37	44.3	12.2
150×75×25	3.2	8.27		10.53	0	2.66	375	83.6	5.97	2.82	50.0	17.3
200×75×20	3.2	9.27		11.81	0	2.19	332	53.8	7.79	2.37	71.6	15.8
200×75×25	3.2	9.52		12.13	0	2.33	736	92.4	7.70	2.76	73.6	17.8

切断・穴孔加工も承ります。

基準長さ 6m、7m、8m、9m、10m、11m、12m
メッキは90g/m²