


H形鋼

建築構造用圧延材 JIS G3136(1994) (SN規格)



細巾系列

シリーズ	サイズ mm					質量 kg/m	断面積 cm ²	断面2次 モーメント cm ⁴		断面2次半径 cm		断面係数 cm ³	
	A	B	t1	t2	r			Ix	Iy	ix	iy	Zx	Zy
100×50	100	50	5	7	8	9.3	11.85	187	14.8	3.98	1.12	37.5	5.91
125×60	125	60	6	8	9	13.2	16.84	413	29.2	4.95	1.32	66.1	9.73
150×75	150	75	5	7	8	14.0	17.85	666	49.5	6.11	1.66	88.8	13.2
175×90	175	90	5	8	8	18.0	2.04	1,210	97.5	7.26	2.06	138	21.7
200×100	198	99	4.5	7	8	17.8	22.69	1,540	113	8.25	2.24	156	22.9
	200	100	5.5	8	8	20.9	26.67	1,810	134	8.23	2.24	181	26.7
250×125	248	124	5	8	8	25.1	31.99	3,450	255	10.4	2.82	288	41.1
	250	125	6	9	8	29.0	36.97	3,960	294	10.4	2.82	317	47.0
300×150	298	149	5.5	8	13	32.0	40.8	6,320	442	12.4	3.29	424	59.3
	300	150	6.5	9	13	36.7	46.78	7,210	508	12.4	3.29	481	67.7
350×175	346	174	6	9	13	41.2	52.45	11,000	791	14.5	3.88	638	91.0
	350	175	7	11	13	49.4	62.91	13,500	984	14.6	3.96	771	112
400×200	396	199	7	11	13	56.1	71.41	19,800	1,450	16.6	4.50	999	145
	400	200	8	13	13	65.4	83.37	23,500	1,740	16.8	4.56	1,170	174
450×200	446	199	8	12	13	65.1	82.97	28,100	1,580	18.4	4.36	1,260	159
	450	200	9	14	13	74.9	95.43	32,900	1,870	18.6	4.43	1,460	187
500×200	496	199	9	14	13	77.9	99.29	40,800	1,840	20.3	4.31	1,650	185
	500	200	10	16	13	88.2	112.2	46,800	2,140	20.4	4.36	1,870	214
	506	201	11	19	13	102	129.3	55,500	2,580	20.7	4.46	2,190	256
600×200	596	199	10	15	13	92.5	117.8	66,600	1,980	23.8	4.10	2,240	199
	600	200	11	17	13	103	131.7	75,600	2,270	24.0	4.16	2,520	227
	606	201	12	20	13	118	149.8	88,300	2,720	24.3	4.26	2,910	270

切断・穴孔・ショット・開先加工も承ります。 基準長さ 6m、7m、8m、9m、10m、11m、12m、13m
上記以上の長尺はお問い合わせ下さい。