

配管用アーク溶接炭素鋼鋼管

STPY400 JIS G3457

呼称	外径 mm	厚さ mm	質量 kg/m	1本当り重量	
				6m	12m
350A	355.6	6.0	51.7	310	
		6.4	55.1	331	
		7.9	67.7	406	
		12.7	107	642	
400A	406.4	6.0	59.2	355	
		6.4	63.1	379	757
		7.9	77.6	466	931
		9.5	93.0	558	
		12.7	123	738	
450A	457.2	6.0	66.8	401	
		6.4	71.1	427	853
		7.9	87.5	525	1050
		9.5	105	630	
		12.7	139	834	
500A	508.0	6.0	74.3	446	
		6.4	79.2	475	950
		7.9	97.4	584	1169
		9.5	117	702	
		12.7	155	930	
550A	558.8	6.4	87.2	523	1046
		7.9	107	642	1284
		9.5	129	774	1548
		12.7	171	1026	2052
600A	609.6	6.0	89.3	536	
		6.4	95.2	571	1142
		7.9	117	702	1404
		9.5	141	846	1692
		12.7	187	1122	2244

呼称	外径 mm	厚さ mm	質量 kg/m	1本当り重量	
				6m	12m
650A	660.4	6.4	103	618	1236
		7.9	127	762	1524
		9.5	152	912	1824
700A	711.2	6.0	104	624	
		6.4	111	666	1332
		7.9	137	822	1644
		9.5	164	984	1968
		12.7	219	1314	2628
750A	762.0	7.9	147	882	1764
		9.5	176	1056	2112
		12.7	235	1410	2820
800A	812.8	7.1	141	846	
		8.0	159	954	1908
		9.5	188	1128	2256
		12.7	251	1506	3012
900A	914.4	8.0	179	1074	2148
		9.5	212	1272	2544
		12.7	282	1692	3384
1000A	1016.0	9.0	223	1338	2676
		9.5	236	1416	2832
		10.3	255	1530	3060
		12.7	314	1884	3768
1100A	1066.0	10.0	273	1638	3276
1200A	1219.2	9.5	283	1698	3396
		11.1	331	1986	3972
		12.7	378	2268	4536