

ガス管 配管用炭素鋼鋼管 SGP JIS G3452 (1988)

JIS呼称 記号A	インチ名 記号B	外径 mm	厚さ mm	質量	1本当り
				kg/m	kg/5.5m
6A	1/8B	10.5	2.0	0.419	2.30
8A	1/4B	13.8	2.3	0.652	3.59
10A	3/8B	17.3	2.3	0.851	4.68
15A	1/2B	21.7	2.8	1.31	7.20
20A	3/4B	27.2	2.8	1.68	9.24
25A	1B	34.0	3.2	2.43	13.4
32A	1 1/4B	42.7	3.5	3.38	18.6
40A	1 1/2B	48.6	3.5	3.89	21.4
50A	2B	60.5	3.8	5.31	29.2
65A	2 1/2B	76.3	4.2	7.47	41.1
80A	3B	89.1	4.2	8.79	48.3
90A	3 1/2B	101.6	4.2	10.1	55.6
100A	4B	114.3	4.5	12.2	67.1
125A	5B	139.8	4.5	15.0	82.5
150A	6B	165.2	5.0	19.8	109
175A	7B	190.7	5.3	24.2	133
200A	8B	216.3	5.8	30.1	166
225A	9B	241.8	6.2	36.0	198
250A	10B	267.4	6.6	42.4	233
300A	12B	318.5	6.9	53.0	292
350A	14B	355.6	7.9	67.7	372
400A	16B	406.4	7.9	77.6	427
450A	18B	457.2	7.9	87.5	481
500A	20B	508.0	7.9	97.4	536

切断・開先加工も承ります。